



Spacers

Solid spacers are available from in a vast array of different materials and thicknesses including FRP, PTFE, HDPE and different types of ferrous and non-ferrous metal. Tri-Clor can also provide armored spacers with different types of metallic and non-metallic substrates. Armored spacers can be lined with FEP, PFA, ETFE, PP Block Copolymer, PVDF, ECTFE, PVC, and CPVC. Computer-aided design and manufacturing is used to cut spacer diameters, holes, or special configurations. Spacers can be drilled with ANSI standard B16.5 150# locations or with special drilling patterns upon requests.

Standard Dimensions of Solid Spacers

Nominal Pipe Size	*Minimum Quantity	**Part Number	***Nominal Thickness	Inside Diameter	Outside Diameter	Bolt Circle Diameter	Number of Holes	Diameter Holes
1/2"	280	0.5-SF-MATL-150-THK		.50"	3.5"	2.38"	4	5/8"
3/4"	280	0.75-SF-MATL-150-THK		.75"	3.88"	2.75"	4	5/8"
1"	180	1-SF-MATL-150-THK		1.0"	4.25"	4.25"	4	5/8"
1 1/4"	125	1.25-SF-MATL-150-THK		1.25"	4.62"	3.50"	4	5/8"
1 1/2"	125	1.5-SF-MATL-150-THK		1.50"	5.00"	3.88"	4	5/8"
2"	90	2-SF-MATL-150-THK		2.0"	6.00"	4.75"	4	3/4"
2 1/2"	70	2.5-SF-MATL-150-THK		2.50"	7.00"	5.50"	4	3/4"
3"	70	3-SF-MATL-150-THK		3.0"	7.50"	6.00"	4	3/4"
4"	55	4-SF-MATL-150-THK		4.0"	9.00"	7.50"	8	3/4"
5"	35	5-SF-MATL-150-THK		5.0"	10.00"	8.50"	8	7/8"
6"	30	6-SF-MATL-150-THK		6.0"	11.00"	9.50"	8	7/8"
8"	10	8-SF-MATL-150-THK		8.0"	13.50"	11.75"	8	7/8"
10"	10	10-SF-MATL-150-THK		10.0"	16.00"	14.25"	12	1.00"
12"	8	12-SF-MATL-150-THK		12.0"	19.00"	17.00"	12	1.00"
14"	8	14-SF-MATL-150-THK		14.0"	21.00"	18.75"	12	1.12"
16"	8	16-SF-MATL-150-THK		16.0"	23.50"	21.25"	16	1.12"
18"	3	18-SF-MATL-150-THK		18.0"	25.00"	22.75"	16	1.25"
20"	3	20-SF-MATL-150-THK		20.0"	27.50"	25.00"	20	1.25"
24"	3	24-SF-MATL-150-THK		24.0"	32.00"	29.50"	20	1.38"
30"	2	30-SF-MATL-150-THK		30.0"	38.75"	36.00"	28	1.38"
36"	2	36-SF-MATL-150-THK		36.0"	46.00"	42.75"	32	1.62"

* Minimum order quantities are subject to change if other sizes of the same thickness are ordered at the same time.

** Material and thickness can vary.

*** Available in nominal sheet thickness.

Chart is for Reference only.



1012 Enterprise Drive
Hastings, Michigan, USA, 49058
Contact Sales @ PH# 269.948.9310
www.tri-clor.com

Request for Quote Form

<i>Nominal Pipe Size</i>	<i>*Quantity Required</i>	<i>*Material of Construction</i>	<i>*Nominal Thickness</i>	<i>*Inside Diameter</i>	<i>*Outside Diameter</i>	<i>*Bolt Circle Diameter</i>	<i>*Number of Holes</i>	<i>*Diameter Holes</i>
1/2"								
3/4"								
1"								
1 1/4"								
1 1/2"								
2"								
2 1/2"								
3"								
4"								
5"								
6"								
8"								
10"								
12"								
14"								
16"								
18"								
20"								
24"								
30"								
36"								

* Required Fields for requesting quotes.
 Please attach any material specifications, special sizes, or drilling requirements
 Return via email to jimt@tri-clor.com or
 Return via email to chad@tri-clor.com or
 Return via email to tim@tri-clor.com



1012 Enterprise Drive
 Hastings, Michigan, USA, 49058
 Contact Sales @ PH# 269.948.9310
www.tri-clor.com